# SAFETY DATA SHEET

# **Husqvarna**<sup>®</sup>

# 1. Identification

Product identifier	Husqvarna Oil Guard 2T Engine Oil
Other means of identification	
Product code	593152701, 593152703, 593152702
Recommended use	Engine oil.
<b>Recommended restrictions</b>	None known.
Manufacturer/Importer/Supplier/	Distributor information
Supplier	Husqvarna Group
Address	9335 Harris Corners Parkway
	Charlotte, NC 28269
	USA
Telephone number	800-487-5951
Emergency telephone number	+1-760-476-3961 (Access code 333721)
2. Hazard(s) identification	
Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statements	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%	
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	> 45	
Distillates (petroleum), hydrotreated middle	64742-46-7	15	
Distillates (pertroluem), hydrotreated light	64742-47-8	10	
Mineral oil	Various	< 2	
Composition comments	All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits. IP346 method DMSO extract for base oil substances: <3.0%.		
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.		

Wash off with soap and water. Get medical attention if irritation develops and persists.
Rinse with water. Get medical attention if irritation develops and persists.
Rinse mouth. Get medical attention if symptoms occur.
Direct contact with eyes may cause temporary irritation. Repeated exposure may cause skin dryness or cracking.
Treat symptomatically.
Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed. Do not direct solid water stream or foam

Move containers from fire area if you can do so without risk. Cool containers exposed to flames

with water until well after the fire is out. Do not point solid water stream directly into burning oil to

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

into hot, burning pools; this may cause frothing and increase fire intensity.

## 6. Accidental release measures

avoid spreading.

Will burn if involved in a fire.

Specific hazards arising from

Special protective equipment and precautions for firefighters

equipment/instructions

Specific methods General fire hazards

media

the chemical

Fire fighting

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Prevent product from entering drains.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Clean contaminated area with oil-removing material.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Avoid direct contact with eyes and prolonged skin exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. The handling temperature should not exceed 140°F/60°C. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities** Store in original tightly closed container. Keep away from heat, sparks and open flame. Store away from incompatible materials (see section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

US. ACGIH Threshold Limit Values				
Туре	Value	Form		
TWA	5 mg/m3	Inhalable fraction.		
oational Health & Safety Code, Sch	redule 1, Table 2)			
Туре	Value	Form		
STEL	10 mg/m3	Mist.		
	Type TWA pational Health & Safety Code, Sch Type	TypeValueTWA5 mg/m3Dational Health & Safety Code, Schedule 1, Table 2)TypeValue		

Product	Туре	/ Code, Schedule 1, Table 2) Value	Form
	TWA	5 mg/m3	Mist.
Canada. British Columbia Safety Regulation 296/97, Product	as amended)	sure Limits for Chemical Substances Value	, Occupational Health and Form
	Туре		-
oil mist (Mineral)	TWA	1 mg/m3	Mist.
Canada. Manitoba OELs (F Product	Reg. 217/2006, The Workpla Type	ace Safety And Health Act) Value	Form
oil mist (Mineral)	TWA	5 mg/m3	Inhalable fraction.
Canada. Ontario OELs. (Co Product	ontrol of Exposure to Biolo Type	ogical or Chemical Agents) Value	Form
oil mist (Mineral)	TWA	5 mg/m3	Inhalable fraction.
Canada. Quebec OELs. (M Product	inistry of Labor - Regulatic Type	on respecting occupational health and Value	d safety) Form
oil mist (Mineral)	STEL TWA	10 mg/m3 5 mg/m3	Mist. Mist.
logical limit values	No biological exposure li	mits noted for the ingredient(s).	
oosure guidelines			
Canada - Alberta OELs: Sk	in designation		
Distillates (pertroluem), 64742-47-8)	hydrotreated light (CAS	Can be absorbed through the ski	n.
64742-47-8)	hydrotreated light (CAS	Can be absorbed through the ski	n.
Canada - Saskatchewan O	•	Can be absorbed through the ski	n
64742-47-8)	hydrotreated light (CAS	Can be absorbed through the ski	
propriate engineering atrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level. Proveasy access to water supply and eye wash facilities.		
ividual protection measures	s, such as personal protect	tive equipment	
Eye/face protection	Wear safety glasses with	n side shields (or goggles).	
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves. Nitrile or neoprene gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves c be recommended by the glove supplier.		
Other	Wear suitable protective clothing. Use of an impervious apron is recommended. Protective cloth should be chemical/oil resistant.		
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.		
Thermal hazards	Wear appropriate therma	al protective clothing, when necessary.	
neral hygiene		rsonal hygiene measures, such as wash ng, and/or smoking. Routinely wash wo	

Appearance			
Physical state	Liquid.		
Form	Clear liquid.		

Colour	Orange.
Odour	Petroleum.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	96.0 °C (204.8 °F) Cleveland open cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower ( %)	Not available.
Explosive limit – upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.8590 (H2O=1)
Relative density temperature	15.6 °C (60.08 °F)
Solubility(ies)	
Solubility (water)	Negligible.
Solubility (other)	Miscible in most petroleum solvents.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	47.5 cSt
Viscosity temperature	40 °C (104 °F)
Other information	
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
10. Stability and reactivity	

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.		
Chemical stability	Material is stable under normal conditions.		
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.		
Conditions to avoid	Contact with incompatible materials. Keep away from heat, sparks and open flame.		
Incompatible materials	Strong oxidising agents. Acids.		
Hazardous decomposition products	Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterised. Sulfur dioxide. Nitrogen oxides. Hydrocarbons. Aldehydes.		

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation	Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing. Prolonged inhalation may be harmful.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation. Repeated exposure may cause skin dryness or cracking.

## Information on toxicological effects

Acute toxicity	Not expected to be acutely to	oxic.
Product	Species	Test Results
Husqvarna Oil Guard 2T Engine O	il (CAS Mixture)	
Acute		
Dermal		
LD50		> 5000 mg/kg
Inhalation		
Vapour		
LD50		> 20 mg/l
Oral		
LD50		> 5000 mg/kg
Skin corrosion/irritation	Repeated exposure may cau	ise skin dryness or cracking.
Serious eye damage/eye irritation	Direct contact with eyes may	cause temporary irritation.
Respiratory or skin sensitisation	ı	
<b>Respiratory sensitisation</b>	Not a respiratory sensitiser.	
Skin sensitisation	This product is not expected	to cause skin sensitisation.
Germ cell mutagenicity	No data available to indicate mutagenic or genotoxic.	product or any components present at greater than 0.1% are
Carcinogenicity	Not classifiable as to carcino	genicity to humans.
ACGIH Carcinogens		
(CAS 64742-54-7)	drotreated heavy paraffinic	A4 Not classifiable as a human carcinogen.
Distillates (petroleum), hy 64742-46-7)	drotreated middle (CAS	A4 Not classifiable as a human carcinogen.
Canada - Manitoba OELs: ca	arcinogenicity	
(CAS 64742-54-7)	drotreated heavy paraffinic	Not classifiable as a human carcinogen.
Distillates (petroleum), hy 64742-46-7)		Not classifiable as a human carcinogen.
• •	Evaluation of Carcinogenicity	
(CAS 64742-54-7)	drotreated heavy paraffinic	3 Not classifiable as to carcinogenicity to humans.
Distillates (petroleum), hy 64742-46-7)	drotreated middle (CAS	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	This product is not expected	to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be	harmful.
Further information		erexposure to oil mists may result in droplet deposition, oil granuloma increased incidence of infection in the respiratory tract.
12. Ecological information	I	

U				
Ecotoxicity	Harmful to a	Harmful to aquatic life with long lasting effects.		
Components		Species	Test Results	
Additive (CAS Proprietary)				
Aquatic				
Acute				
Crustacea	EC50	Daphnia	0.037 mg/l, 48 hours	
Chronic				
Crustacea	NOEC	Daphnia	0.0037 mg/l, 21 days	
Persistence and degradability	This produc	t is partially biodegradable.		

Bioaccumulative potential	No data available on bioaccumulation.
Mobility in soil	The product is insoluble or slightly soluble in water.
Other adverse effects	Oil spills are generally hazardous to the environment. The product contains volatile organic compounds which have a photochemical ozone creation potential.

# 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport information

TDG

Not regulated as dangerous goods.

#### ΙΑΤΑ

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

# Transport in bulk according to<br/>Annex II of MARPOL 73/78 and<br/>the IBC CodeNot established.

## 15. Regulatory information

#### **Canadian regulations**

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

#### Controlled Drugs and Substances Act Not regulated. Export Control List (CEPA 1999, Schedule 3)

Not listed.
Greenhouse Gases
Not listed.
Precursor Control Regulations

Not regulated.

International regulations

**Stockholm Convention** 

Not applicable.

Rotterdam Convention

Not applicable. Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

#### International Inventories

**Country(s) or region** Canada Canada

#### Inventory name

Domestic Substances List (DSL) Non-Domestic Substances List (NDSL)

# On inventory (yes/no)\* Yes No

#### Country(s) or region

#### Inventory name

#### United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information

Issue date	02-March-2018
Revision date	-
Version No.	01
Disclaimer	Husqvarna Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.